

Attorney Docket No. 12000US03

Patent

AMENDMENTS TO THE SPECIFICATION

On p. 15 of the specification, please replace the first complete paragraph with the paragraph on the following page.

Attorney Docket No. 12000US03

Patent

A further modification of the foregoing echo canceller system relates to the value stored as E_{max} at the instant of tap coefficient transfer. Instead of setting E_{max} equal to the \hat{E} value at the transfer instant, E_{max} may be set to a value equal to the value of \hat{E} minus a constant value (e.g., one, three, or 6 dB). At no time, however, should the E_{max} value be set to a value that is below the lower bound value for E_{max} . Additionally, a further condition may be imposed in that a new softened E_{max} is not less than the prior value of E_{max} . The foregoing "softening" of the E_{max} value increases the number of transfers that occur and, further, provides more decision-making weight to the condition of \hat{E} being larger than \bar{E} . Further details with respect to the operation of the echo canceller coefficient transfer process are set forth and in the co-pending patent application titled "ECHO CANCELLER HAVING THE IMPROVED TAP COEFFICIENT TRANSFER", (~~Attorney Docket No. —~~) filed on ~~even date herewith~~ November 14, 1997, Serial No. 08/970,230, now U.S. Patent No. 6,181,793 B1.

Attorney Docket No. 12000US03

-4-

Attorney Docket No. 12000US03

Patent

On p. 19 of the specification, please replace the first paragraph with the paragraph on the following page.

Attorney Docket No. 12000US03

Patent

A still further manner of detecting a double-talk condition is set forth in U.S.N. Serial No. 08/971,116, now U.S. Patent No. 6,266,409 B1, titled "ECHO CANCELLER EMPLOYING DUAL-H ARCHITECTURE HAVING IMPROVED DOUBLE-TALK" (~~Attorney Docket No.~~), filed on November 14, 1997, the teachings of which are hereby incorporated by reference. As set forth in that patent application, a double-talk condition is declared based on certain monitored filtered performance parameters.